

| Volkswagen | Audi | SEAT | ŠKODA |



Platinum Plus 5W-30 fully synthetic engine oil with QFX® technology

A premium, high-performance, low-ash engine oil for petrol and diesel engines with particulate filters, specially developed for Audi, BMW, Mercedes-Benz, SEAT, ŠKODA, Vauxhall (GM) and VW.

Description

Quantum Platinum Plus 5W-30 is a premium, high-performance engine oil designed for passenger cars and light commercial vehicles, manufactured using Quantum QFX® technology. QFX® provides significant performance benefits compared to conventional oils. These benefits include the highest performance for the entire oil drain period, improved fuel economy, reduced wear and easier cold starts even at very low temperatures.

Application

Quantum Platinum Plus 5W-30 satisfies the requirements of vehicles fitted with exhaust gas aftertreatment devices such as SCR and DPF. As well as being approved for use in VW, Audi, BMW, Porsche and ŠKODA, it is also suitable for use in any vehicle where ACEA C3 is the requirement. It should only be used in diesel engines running on low sulphur fuel. Quantum Platinum Plus 5W-30 will mix with other oil but to gain the full benefit and to fully utilise the QFX® technology, it is recommended to change the oil completely when changing to the Quantum grade.

Key Points

Improves performance by enabling:

- Faster oil circulation for easier start-ups
- Lower fuel consumption
- Reduced oil consumption
- Better engine protection by use of advanced additive technology.

Platinum Plus 5W-30

Pack

Typical Values

| Part Number | Volume |
|----------------|--------|
| ZGB115QLB01621 | 1L |
| ZGB115QLB01625 | 5L |
| ZGB115QLB01622 | 20L |
| ZGB115QLB01623 | 208L |
| ZGB115QLB01624 | Bulk |

| Test | Unit | Method | Result |
|-----------------------------|-------|--------------|--------|
| Density @ 15°C | g/ml | DIN 51757 | 0.850 |
| Kinematic Viscosity @ 40°C | mm2/s | DIN 51562-1 | 67.2 |
| Kinematic Viscosity @ 100°C | mm2/s | DIN 51562-1 | 11.8 |
| Viscosity Index | | DIN ISO 2909 | 173 |
| Flash Point (Open) | °C | DIN ISO 2592 | 230 |

Performance Profile

Specifications

ACEA C3 API SN / SM

Approvals

BMW Longlife-04 GM dexos2[™] (D20214GL156) VW 502 00 / 505 00 / 505 01

Recommendations

Fiat 9.55535-S3 Ford M2C917-A GM-LL-A-025 / GM-LL-B-025 MB 229.51 / 229.52 Safety data sheets can be found on the Quantum website.

For current trade pricing, please refer to the separate price sheets.

Quantum is a registered trade mark of Volkswagen Group United Kingdom Limited, Yeomans Drive, Blakelands, Milton Keynes MK14 5AN.

For any technical queries regarding this product contact the Quantum Technical Helpline 01782 203717.

Find the right oil for your vehicle:

quantumparts.co.uk



