

# SAFETY DATA SHEET ZGB00QMAFL5LNW MAINTENANCE FLUID 5L

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name ZGB00QMAFL5LNW MAINTENANCE FLUID 5L

Product No. 003098000009

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Universal lubricant.

#### 1.3. Details of the supplier of the safety data sheet

Supplier Volkswagen Group UK Limited

Yeomans Drive Blakeland Milton Keynes MK14 5AN +44 (0) 800 333666

#### 1.4. Emergency telephone number

National Emergency Telephone Number Hazchem line: 0044 (0) 7970 779978

#### **SECTION 2: HAZARDS IDENTIFICATION**

# 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Flam. Liq. 3 - H226

Human health EUH066;STOT SE 3 - H336;Asp. Tox. 1 - H304

Environment Not classified.

Classification (1999/45/EEC) Xn;R65. R10, R66, R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

# 2.2. Label elements

Contains NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Label In Accordance With (EC) No. 1272/2008



Signal Word Danger

Hazard Statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

**Precautionary Statements** 

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing vapour/spray.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

# **ZGB00QMAFL5LNW MAINTENANCE FLUID 5L**

P501 Dispose of contents/container in accordance with local regulations.

Supplementary Precautionary Statements

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P403+235 Store in a well-ventilated place. Keep cool.

Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains:

SOL109 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics

(2-25%).

#### 2.3. Other hazards

#### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

MINERAL OIL (REFINED) 1-5%

CAS-No.: 64742-52-5 EC No.: 265-155-0

Classification (EC 1272/2008) Classification (67/548/EEC)

Not classified. Not classified.

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY 60-100%

CAS-No.: 64742-48-9 EC No.: 919-857-5 Registration Number: 01-2119463258-33-xxxx

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Liq. 3 - H226 Xn;R65. EUH066 R10,R66,R67.

STOT SE 3 - H336 Asp. Tox. 1 - H304

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

# **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

# 4.2. Most important symptoms and effects, both acute and delayed

# 4.3. Indication of any immediate medical attention and special treatment needed

# **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1. Extinguishing media

# 5.2. Special hazards arising from the substance or mixture

#### 5.3. Advice for firefighters

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

# 6.2. Environmental precautions

# ZGB00QMAFL5LNW MAINTENANCE FLUID 5L

#### 6.3. Methods and material for containment and cleaning up

# 6.4. Reference to other sections

# **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

# 7.2. Conditions for safe storage, including any incompatibilities

#### 7.3. Specific end use(s)

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
MINERAL OIL (REFINED)			5 mg/m3		10 mg/m3	
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY			1000 mg/m3			

#### 8.2. Exposure controls

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1. Information on basic physical and chemical properties

#### 9.2. Other information

# **SECTION 10: STABILITY AND REACTIVITY**

- 10.1. Reactivity
- 10.2. Chemical stability
- 10.3. Possibility of hazardous reactions
- 10.4. Conditions to avoid
- 10.5. Incompatible materials
- 10.6. Hazardous decomposition products

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1. Information on toxicological effects

# **SECTION 12: ECOLOGICAL INFORMATION**

- 12.1. Toxicity
- 12.2. Persistence and degradability
- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil

# **ZGB00QMAFL5LNW MAINTENANCE FLUID 5L**

#### 12.5. Results of PBT and vPvB assessment

# 12.6. Other adverse effects

# **SECTION 13: DISPOSAL CONSIDERATIONS**

# 13.1. Waste treatment methods

# **SECTION 14: TRANSPORT INFORMATION**

#### 14.1. UN number

- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
- 14.4. Packing group
- 14.5. Environmental hazards
- 14.6. Special precautions for user
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

# **SECTION 15: REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.2. Chemical Safety Assessment

# **SECTION 16: OTHER INFORMATION**

Risk Phrases In Full

R10 Flammable.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.