



**for Volkswagen Group**  
Genuine Parts



# LONGLIFE III 5W-30

## Fully synthetic engine oil



Premium High-Performance, low-ash engine oil for petrol and diesel engines. Specially developed for long-life service intervals and vehicles with diesel particulate filters. Approved for Audi, BMW, Porsche, SEAT, Skoda and VW. Also suitable for Mercedes-Benz.

### Description

Quantum Longlife III 5W-30 is a premium high-performance engine oil designed for passenger cars and light commercial vehicles and manufactured using Quantum QFX technology. QFX provides significant performance benefits compared to conventional oils. These benefits including the highest performance for the entire oil drain period, improved fuel economy, reduced wear and easier cold starts even at very low temperatures.

### Application

Quantum Longlife III 5W-30 satisfies the requirements of vehicles fitted with exhaust gas aftertreatment devices such as SCR and DPF. As well as being approved for use in VW, Audi, BMW, Porsche and Skoda Quantum Longlife III 5W-30 is also suitable for use in any vehicle where ACEA C3 is the requirement. Quantum Longlife III 5W-30 should only be used in diesel engines running on low sulphur fuel. Quantum Longlife III 5W-30 will mix with other oil but to gain the full benefit and to fully utilise the QFX Technology. It is recommended to change the oil completely when changing to the Quantum grade.

### Key Points

Improves performance by enabling:

- Faster oil circulation for easier start-ups
- Lower fuel consumption
- Reduced oil consumption
- Better engine protection by use of advanced additive technology



**for Volkswagen Group**  
Genuine Parts



# LONGLIFE III 5W-30

## Fully synthetic engine oil

### Pack

Part Number	Volume
ZGB115QLB01500	1L
ZGB115QLB01505	5L
ZGB115QLB01502	20L
ZGB115QLB01503	208L
ZGB115QLB01504	Bulk

### Typical Values

Test	Unit	Method	Result
Density @ 15°C	g/ml	DIN 51757	0.851
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	DIN 51562-1	61.0
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	DIN 51562-1	11.7
Viscosity Index		DIN ISO 2909	191
Flash Point (Open)	°C	DIN ISO 2592	230

### Performance Profile

#### Specifications

ACEA C3  
API SN

#### Approvals

BMW LONGLIFE-04  
PORSCHE C30  
VW 504 00 / 507 00

#### Recommendations

CHRYSLER MS-11106  
FIAT 9.55535-S3  
MERCEDES MB 229.51 / 229.52

Safety data sheets can be found on the Quantum website.

Quantum is a registered trade mark of Volkswagen Group United Kingdom Limited, Yeomans Drive, Blakelands, Milton Keynes MK14 5AN.

For any technical queries regarding this product  
**please contact [quantum@vwg.co.uk](mailto:quantum@vwg.co.uk)**

**Find the right oil for your vehicle:**

<https://tps.trade/oil-search>

**Contact your local TPS Centre to find out more, or visit [tps.trade](https://tps.trade)**