

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 16

LOCTITE 268

SDS No. : 153641 V005.0 Revision: 21.11.2016 printing date: 13.09.2017 Replaces version from: 27.01.2015

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### 1.1. Product identifier

LOCTITE 268

#### **Contains:**

A mixture of: N,N'-Ethane-1,2-diylbis(decanamide); 12-Hydroxy-N-[2-[1-oxydecyl)amino]ethyl]octadecanamide; N,N'-Ethane-1,2-diylbis(1

**1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use:

Threadlocker

## 1.3. Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone:	+44 1442 278000
Fax-no.:	+44 1442 278071

ua-productsafety.uk@uk.henkel.com

### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification (CLP):	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

### 2.2. Label elements

Label elements (CLP):

Hazard pictogram:		
Signal word:	Warning	

Hazard statement:	H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Precautionary statement: Prevention	P280 Wear protective gloves. P273 Avoid release to the environment.
Precautionary statement: Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

#### 2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

General chemical description: Threadlocker Stick

# Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
A mixture of: N,N'-Ethane-1,2- diylbis(decanamide); 12-Hydroxy-N-[2-[1- oxydecyl)amino]ethyl]octadecanamide; N,N'-Ethane-1,2-diylbis(1	430-050-2	10- < 20 %	Skin Sens. 1 H317 Aquatic Chronic 2 H411
Cumene hydroperoxide 80-15-9	201-254-7	0,1- < 1 %	Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314
N,N-Diethyl-p-toluidine 613-48-9	210-345-0	0,1-< 1 %	Acute Tox. 3; Oral H301 Acute Tox. 3; Dermal H311 Acute Tox. 3; Inhalation H331 STOT RE 2 H373 Aquatic Chronic 3 H412
1-Methyl-2-pyrrolidone 872-50-4	212-828-1 01-2119472430-46	0,1- < 1 %	Repr. 1B H360D Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 ===== EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)
N,N-dimethyl-o-toluidine 609-72-3	210-199-8	0,1-< 1%	Acute Tox. 3; Inhalation H331 Acute Tox. 3; Dermal H311 Acute Tox. 3; Oral H301 STOT RE 2 H373 Aquatic Chronic 3 H412
1,4-Naphthalenedione 130-15-4	204-977-6	100- < 250 PPM	Acute Tox. 3; Oral H301 Skin Irrit. 2; Dermal H315 Skin Sens. 1; Dermal H317 Eye Irrit. 2 H319 Acute Tox. 1; Inhalation H330 STOT SE 3; Inhalation H335 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

Prolonged or repeated contact may cause eye irritation.

## 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## **SECTION 5: Firefighting measures**

**5.1. Extinguishing media Suitable extinguishing media:** Carbon dioxide, foam, powder Fine water spray

**Extinguishing media which must not be used for safety reasons:** None known

5.2. Special hazards arising from the substance or mixture
In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.
5.3. Advice for firefighters
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### Additional information:

In case of fire, keep containers cool with water spray.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear protective equipment. Ensure adequate ventilation.

#### **6.2.** Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. See advice in section 8

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Use only in well-ventilated areas. Avoid skin and eye contact. Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation. See advice in section 8

#### Hygiene measures:

Good industrial hygiene practices should be observed. Do not eat, drink or smoke while working. Wash hands before work breaks and after finishing work.

## 7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction. Store in a cool, well-ventilated place.

**7.3. Specific end use(s)** Threadlocker

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	[Regulated substance] ppm mg/m <sup>3</sup> Value type		Short term exposure limit category / Remarks	Regulatory list	
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Ethene, homopolymer 9002-88-4 [DUST, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Ethene, homopolymer 9002-88-4 [DUST, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
I-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]	20	80	Short Term Exposure Limit (STEL):		EH40 WEL
I-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]	10	40	Time Weighted Average (TWA):		EH40 WEL
I-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
I-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]	10	40	Time Weighted Average (TWA):	Indicative	ECTLV
1-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]	20	80	Short Term Exposure Limit (STEL):	Indicative	ECTLV
1-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]			Skin designation:	Can be absorbed through the skin.	ECTLV
Cumene 98-82-8 [CUMENE]	50	250	Short Term Exposure Limit (STEL):		EH40 WEL
Cumene 98-82-8 [CUMENE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Cumene 98-82-8 [CUMENE]	25	125	Time Weighted Average (TWA):		EH40 WEL
Cumene 98-82-8 [CUMENE]	50	250	Short Term Exposure Indicative Limit (STEL):		ECTLV
Cumene 98-82-8 [CUMENE]	20	100	Time Weighted Average (TWA):	Indicative	ECTLV

## **Occupational Exposure Limits**

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE		2,4	Time Weighted Average (TWA):		IR_OEL

DUST]					
Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, RESPIRABLE]		4	Time Weighted Average (TWA):		IR_OEL
Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		IR_OEL
1-Methyl-2-pyrrolidone 872-50-4 [1-METHYL-2-PYRROLIDONE]	10	40	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
1-Methyl-2-pyrrolidone 872-50-4 [1-METHYL-2-PYRROLIDONE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
1-Methyl-2-pyrrolidone 872-50-4 [1-METHYL-2-PYRROLIDONE]	20	80	Short Term Exposure Limit (STEL):	Indicative OELV	IR_OEL
1-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]	10	40	Time Weighted Average (TWA):	Indicative	ECTLV
1-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]	20	80	Short Term Exposure Limit (STEL):	Indicative	ECTLV
1-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]			Skin designation:	Can be absorbed through the skin.	ECTLV
Cumene 98-82-8 [ISOPROPYL BENZENE]	20	100	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Cumene 98-82-8 [ISOPROPYL BENZENE]	50	250	Short Term Exposure Limit (STEL):	Indicative OELV	IR_OEL
Cumene 98-82-8 [ISOPROPYL BENZENE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Cumene 98-82-8 [CUMENE]	50	250	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Cumene 98-82-8 [CUMENE]	20	100	Time Weighted Average (TWA):	Indicative	ECTLV

## Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value		Remarks		
			mg/l	ppm	mg/kg	others	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (freshwater)					0,0031 mg/L	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (marine water)					0,00031 mg/L	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (intermittent releases)					0,031 mg/L	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	Sewage treatment plant					0,35 mg/L	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	sediment (freshwater)				0,023 mg/kg		
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	sediment (marine water)				0,0023 mg/kg		
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	soil				0,0029 mg/kg		
1-Methyl-2-pyrrolidone 872-50-4	aqua (freshwater)					0,25 mg/L	
1-Methyl-2-pyrrolidone 872-50-4	aqua (marine water)					0,025 mg/L	
1-Methyl-2-pyrrolidone 872-50-4	aqua (intermittent releases)					5 mg/L	
1-Methyl-2-pyrrolidone 872-50-4	sediment (freshwater)				0,805 mg/kg		
1-Methyl-2-pyrrolidone 872-50-4	soil				0,138 mg/kg		
1-Methyl-2-pyrrolidone 872-50-4	sewage treatment plant (STP)					10 mg/L	
1-Methyl-2-pyrrolidone 872-50-4	oral				0,00167 mg/kg		
1-Methyl-2-pyrrolidone 872-50-4	sediment (marine water)				0,0805 mg/kg		

## **Derived No-Effect Level (DNEL):**

Name on list	ist Application Area Route of Health Effect Exposure Time		Value	Remarks	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	Workers	inhalation	Long term exposure - systemic effects	6 mg/m3	
1-Methyl-2-pyrrolidone 872-50-4	Workers	dermal	Acute/short term exposure - systemic effects	208 mg/kg bw/day	
1-Methyl-2-pyrrolidone 872-50-4	Workers	Inhalation	Acute/short term exposure - systemic effects	80 mg/m3	
1-Methyl-2-pyrrolidone 872-50-4	Workers	dermal	Long term exposure - systemic effects	19,8 mg/kg bw/day	
1-Methyl-2-pyrrolidone 872-50-4	Workers	Inhalation	Long term exposure - systemic effects	40 mg/m3	
1-Methyl-2-pyrrolidone 872-50-4	General population	dermal	Acute/short term exposure - systemic effects	125 mg/kg bw/day	
1-Methyl-2-pyrrolidone 872-50-4	General population	Inhalation	Acute/short term exposure - systemic effects	80 mg/m3	
1-Methyl-2-pyrrolidone 872-50-4	General population	oral	Acute/short term exposure - systemic effects	26 mg/kg bw/day	
1-Methyl-2-pyrrolidone 872-50-4	General population	dermal	Long term exposure - systemic effects	11,9 mg/kg bw/day	
1-Methyl-2-pyrrolidone 872-50-4	General population	Inhalation	Long term exposure - systemic effects	12,5 mg/m3	
1-Methyl-2-pyrrolidone 872-50-4	General population	oral	Long term exposure - systemic effects	6,3 mg/kg bw/day	

# **Biological Exposure Indices:**

None

## 8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection: Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

#### Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance	solid material
	wax
	red
Odor	mild
Odour threshold	No data available / Not applicable
pH	Not applicable
Initial boiling point	> 149 °C (> 300.2 °F)
Flash point	Not applicable
Decomposition temperature	No data available / Not applicable
Vapour pressure	< 6,67 mbar
(20 °C (68 °F))	
Density	1,07 g/cm3
0	
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Slight
(Solvent: Water)	
Solubility (qualitative)	Not applicable
(Solvent: Acetone)	
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

## 9.2. Other information

No data available / Not applicable

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Strong oxidizing agents.

**10.2. Chemical stability** Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

No decomposition if used according to specifications.

#### **10.5. Incompatible materials**

See section reactivity.

#### 10.6. Hazardous decomposition products

carbon oxides.

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### Inhalative toxicity:

May cause irritation to respiratory system.

#### Skin irritation:

Prolonged or repeated contact may cause skin irritation.

#### Eye irritation:

Prolonged or repeated contact may cause eye irritation.

#### Sensitizing:

May cause an allergic skin reaction.

#### Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	LD50	550 mg/kg	oral		rat	not specified
1-Methyl-2-pyrrolidone 872-50-4	LD50	4.150 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
1,4-Naphthalenedione 130-15-4	LD50	190 mg/kg	oral		rat	not specified

### Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
1-Methyl-2-pyrrolidone 872-50-4	LC50	> 5,1 mg/l	aerosol	4 h		OECD Guideline 403 (Acute Inhalation Toxicity)

#### Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	LD50	1.200 - 1.520 mg/kg	dermal			not specified
1-Methyl-2-pyrrolidone 872-50-4	LD50	> 5.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)

#### Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
1-Methyl-2-pyrrolidone 872-50-4	irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1-Methyl-2-pyrrolidone 872-50-4	moderately irritating		human	not specified

## Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
1-Methyl-2-pyrrolidone 872-50-4	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

## Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
1-Methyl-2-pyrrolidone 872-50-4	not sensitising	Mouse local lymphnod	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
		e assay (LLNA)		

#### Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	not specified
1-Methyl-2-pyrrolidone negative 872-50-4	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	without		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1-Methyl-2-pyrrolidone 872-50-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
	negative	oral: gavage		hamster, Chinese	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)

### **Repeated dose toxicity**

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified
1-Methyl-2-pyrrolidone 872-50-4	NOAEL=0,5 mg/l	inhalation	90 days6 hrs/day, 5 days/wk	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

## **SECTION 12: Ecological information**

#### General ecological information:

In the cured state contribution of this product to Environmental Hazards is insignificant in comparison to articles in which it is used.

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

### 12.1. Toxicity

## Ecotoxicity:

Do not empty into drains / surface water / ground water. Harmful to aquatic life with long lasting effects.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
			Study			
Cumene hydroperoxide	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
80-15-9						203 (Fish, Acute
	l l					Toxicity Test)
Cumene hydroperoxide	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
80-15-9						202 (Daphnia sp.
						Acute
						Immobilisation
~						Test)
Cumene hydroperoxide	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline
80-15-9						201 (Alga, Growth
Commence bandress services its	EC10	70	Bacteria	30 min		Inhibition Test)
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min		not specified
1-Methyl-2-pyrrolidone	LC50	4.000 mg/l	Fish	96 h	Leuciscus idus	DIN 38412-15
872-50-4	LC50	4.000 mg/1	14811	90 11	Leuciscus idus	DIN 36412-13
1-Methyl-2-pyrrolidone	EC50	4.897 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
872-50-4	Leso	1.097 mg I	Dupinnu	10 11	Dupiniu niugiu	202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
1-Methyl-2-pyrrolidone	EC50	> 500 mg/l	Algae	72 h	Scenedesmus subspicatus (new	DIN 38412-09
872-50-4					name: Desmodesmus	
					subspicatus)	
1-Methyl-2-pyrrolidone	NOEC	12,5 mg/l	chronic	21 d	Daphnia magna	OECD 211
872-50-4			Daphnia			(Daphnia magna,
						Reproduction Test)
1,4-Naphthalenedione	EC50	0,011 mg/l	Algae	72 h	Dunaliella bioculata	OECD Guideline
130-15-4						201 (Alga, Growth
l					l	Inhibition Test)

## 12.2. Persistence and degradability

## Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1-Methyl-2-pyrrolidone 872-50-4	inherently biodegradable	aerobic	> 90 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
	readily biodegradable	aerobic	92 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
1,4-Naphthalenedione 130-15-4		no data	0 - 60 %	OECD 301 A - F

## 12.3. Bioaccumulative potential / 12.4. Mobility in soil

#### Mobility:

Cured adhesives are immobile.

#### **Bioaccumulative potential:**

No data available.

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

Cumene hydroperoxide 80-15-9 Cumene hydroperoxide 80-15-9	2,16	9,1	calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test) not specified
1-Methyl-2-pyrrolidone 872-50-4	-0,46			25 °C	OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)
1,4-Naphthalenedione 130-15-4	1,71				not specified

## 12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
Cumene hydroperoxide	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
80-15-9	Bioaccumulative (vPvB) criteria.
1-Methyl-2-pyrrolidone	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
872-50-4	Bioaccumulative (vPvB) criteria.

#### 12.6. Other adverse effects

No data available.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

# **SECTION 14: Transport information** 14.1. UN number Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.2. UN proper shipping name Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.3. Transport hazard class(es) Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.4. Packing group Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.5. **Environmental hazards** Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.6. Special precautions for user Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code not applicable

## **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture VOC content < 3 % (2010/75/EC)

## 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows: H242 Heating may cause a fire. H301 Toxic if swallowed. H302 Harmful if swallowed. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H330 Fatal if inhaled. H331 Toxic if inhaled. H335 May cause respiratory irritation. H360D May damage the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

#### Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.