



for Volkswagen Group
Genuine Parts



PLATINUM PLUS 5W-40

Fully synthetic engine oil



A Premium High-Performance low-ash engine oil specifically designed for petrol engines, diesel engines with particulate filters, and engines with turbochargers. This oil is approved for use in many modern vehicles including Audi, BMW, Porsche, Renault, SEAT, Skoda, VW. Also suitable for Mercedes-Benz, Vauxhall and Fiat.

Description

Quantum Platinum Plus 5W-40 is a premium high-performance engine oil designed for passenger cars and light commercial vehicles and manufactured using Quantum QFX technology. QFX provides significant performance benefits compared to conventional oils. These benefits including the highest performance for the entire oil drain period, improved fuel economy, reduced wear and easier cold starts even at very low temperatures. Platinum Plus 5W-40 is suitable for use in highly stressed downsized engines and with stop-start systems.

Application

Quantum Platinum Plus 5W-40 satisfies the requirements of vehicles fitted with exhaust gas aftertreatment devices such as SCR and DPF. As well as being approved for use in VW, Audi, Porsche, Seat and Skoda Quantum Platinum Plus 5W-40 is also suitable for use in Mercedes Benz, Fiat and any vehicle where ACEA C3 is the requirement. Quantum Platinum 5W-40 should only be used in diesel engines running on low sulphur fuel. Quantum Platinum Plus 5W-40 will mix with other oil but to gain the full benefit and to fully utilise the QFX Technology it is recommended to change the oil completely when changing to the Quantum grade.

Key Points

Improves performance by enabling:

- Flexible use for petrol and diesel engines including those fitted with catalysts and particulate filters
- Excellent wear protection
- Reduced oil consumption
- Especially suited to high performance VW group engines



for Volkswagen Group
Genuine Parts



PLATINUM PLUS 5W-40

Fully synthetic engine oil

Pack

Part Number	Volume
ZGB115QLB01529	1L
ZGB115QLB01526	5L
ZGB115QLB01527	20L
ZGB115QLB01528	208L
ZGB115QLB01530	Bulk

Typical Values

Test	Unit	Method	Result
Density @ 15°C	g/ml	DIN 51757	0.850
Kinematic Viscosity @ 40°C	mm ² /s	DIN 51562-1	72.6
Kinematic Viscosity @ 100°C	mm ² /s	DIN 51562-1	13.1
Viscosity Index		DIN ISO 2909	185
Flash Point (Open)	°C	DIN ISO 2592	220

Performance Profile

Specifications

ACEA C3
API SN
API CF

Approvals

BMW LL-04
PORSCHE C40
RENAULT RN0700 /
RN0710
VW 511 00

Recommendations

CHRYSLER MS-10725
FIAT 9.55535-S2 / T2 / GH2
MERCEDES MB 226.5 / MB 229.31 / 229.51
/ 229.52
FORD WSS-M2C917-A
VW 505 00 / 505 01

Safety data sheets can be found on the Quantum website.

Quantum is a registered trade mark of Volkswagen Group United Kingdom Limited,
Yeomans Drive, Blakelands, Milton Keynes MK14 5AN.

For any technical queries regarding this product
please contact quantum@vwg.co.uk

Find the right oil for your vehicle:

<https://tps.trade/oil-search>

Contact your local TPS Centre to find out more, or visit tps.trade