





A Fully Synthetic High-Performance low-ash engine oil specially developed for use in Renault and PSA petrol and diesel engines with exhaust aftertreatment and turbochargers. Excellent cold start, reduced oil consumption and helps reduce exhaust emissions.

### **Description**

Quantum SYNTA RN 5W-30 is a fully synthetic engine oil with excellent fueleconomy designed for use in passenger cars and light commercial vehicles.

Quantum Synta RN 5W-30 is specially developed for PSA and RENAULT vehicles with exhaust after treatment and turbocharger. Quantum SYNTA RN 5W-30 provides excellent wear protection, engine cleanliness, reduces deposits and varnish and protects from corrosion. Also suitable for use in certain hybrid vehicles of different manufacturers.

### **Application**

Quantum SYNTA RN 5W-30 is suitable for vehicles running on petrol, diesel, and gas (LPG, CNG) and with modern exhaust aftertreatment devices. Quantum SYNTA RN 5W-30 can be used for all Renault petrol engines (except RS and Alpine), Euro 6 diesel engines and some older models without particulate filters. Check website lookup to confirm. Quantum SYNTA RN 5W-30 is also suitable for use in any vehicle where ACEA C2/C3 is specified. Quantum SYNTA RN 5W-30 will mix with other oil but to gain the full benefit, it is recommended to change the oil completely when changing to the Quantum grade.

### **Key Points**

- Especially developed for Renault and PSA engines
- Lower fuel consumption and improved exhaust emissions
- Reduced oil consumption and internal engine deposits
- Ideal for mixed OEM fleets
- Suitable for certain hybrid vehicles, subject to OEM requirements





## **SYNTA RN 5W-30**

# Fully synthetic engine oil

### Pack

Part Number	Volume
ZGB115QLB03031	1L
ZGB115QLB03032	5L
ZGB115QLB03033	20L
ZGB115QLB03034	208L

### Typical Values

Test	Unit	Method	Result
Density @ 15°C	g/ml	DIN 51757	0.849
Kinematic Viscosity @ 40°C	mm²/s	DIN 51562-1	70.9
Kinematic Viscosity @ 100°C	mm²/s	DIN 51562-1	12.0
Viscosity Index		DIN ISO 2909	167
HTHS	mPas	ASTM D4683	≥3.5
Sulphated ash	% m/m	DIN 51575	≤0.8

### Performance Profile

#### **Specifications**

ACEA C2/C3 API SP

### **Approvals**

PSA B71 2290 RENAULT RN17

### **Recommendations**

FIAT 9.55535-S1 MERCEDES MB 229.31 / 229.51 / 229.52 / 226.52 RENAULT RN0700/0710

#### Safety data sheets can be found on the Quantum website.

Quantum is a registered trade mark of Volkswagen Group United Kingdom Limited, Yeomans Drive, Blakelands, Milton Keynes MK14 5AN.

For any technical queries regarding this product

 $please\,contact\,quantum@vwg.co.uk$ 

Find the right oil for your vehicle:

https://tps.trade/oil-search