

**LOCTITE 648** 

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 20

SDS No.: 153474

V005.0

Revision: 16.06.2017

printing date: 13.09.2017

Replaces version from: 27.10.2016

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE 648

#### **Contains:**

2,2'-Ethylenedioxydiethyl dimethacrylate

Acrylic acid

Hydroxypropyl methacrylate

Acetic acid, 2-phenylhydrazide

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Adhesive

# 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

# 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

# $\textbf{Classification} \ (\textbf{CLP}) \textbf{:}$

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye damage Category 1

H318 Causes serious eye damage.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation.

Target organ: respiratory tract irritation

Chronic hazards to the aquatic environment Category 3

H412 Harmful to aquatic life with long lasting effects.

MSDS-No.: 153474 LOCTITE 648 Page 2 of 20

V005.0

#### 2.2. Label elements

#### **Label elements (CLP):**



Signal word:	Danger
Hazard statement:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.
Precautionary statement:	"***" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements***
Precautionary statement: Prevention	P261 Avoid breathing vapours. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection.
Precautionary statement: Response	P302+P352 IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

#### 2.3. Other hazards

Non corrosive to skin in accordance with the in vitro test method, B40 skin corrosion - Human skin model assay, equivalent to test method OECD 431 or based on analogy to similar products tested.

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. None if used properly.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

## General chemical description:

Methacrylate resin based product containing Acrylic Acid

MSDS-No.: 153474 LOCTITE 648 Page 3 of 20

V005.0

# Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	203-652-6 01-2119969287-21	10- 20 %	Skin Sens. 1B H317
Acrylic acid 79-10-7	201-177-9 01-2119452449-31	5-< 10 %	Flam. Liq. 3 H226 Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Corr. 1A H314 Acute Tox. 4; Inhalation H332 STOT SE 3 H335 Aquatic Acute 1 H400 Aquatic Chronic 2 H411
Hydroxypropyl methacrylate 27813-02-1	248-666-3 01-2119490226-37	5-< 10 %	Skin Sens. 1 H317 Eye Irrit. 2 H319
Cumene hydroperoxide 80-15-9	201-254-7	1-< 3 %	Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314
Acetic acid, 2-phenylhydrazide 114-83-0	204-055-3	0,1-< 1 %	Acute Tox. 3; Oral  H301  Skin Irrit. 2  H315  Skin Sens. 1  H317  Eye Irrit. 2  H319  STOT SE 3; Inhalation  H335  Carc. 2  H351
Methacrylic acid 79-41-4	201-204-4 01-2119463884-26	0,1-< 1 %	Acute Tox. 4; Oral H302 Acute Tox. 3; Dermal H311 Acute Tox. 4; Inhalation H332 Skin Corr. 1A H314
1,4-Naphthalenedione 130-15-4	204-977-6	100- < 250 PPM	Acute Tox. 3; Oral H301 Skin Irrit. 2; Dermal H315 Skin Sens. 1; Dermal H317 Eye Irrit. 2 H319 Acute Tox. 1; Inhalation H330 STOT SE 3; Inhalation H335 Aquatic Acute 1

MSDS-No.: 153474 LOCTITE 648 Page 4 of 20

V005.0

	H400
	Aquatic Chronic 1
	H410
	M factor (Acute Aquat Tox): 10 M factor
	(Chron Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

# 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

Carbon dioxide, foam, powder

#### Extinguishing media which must not be used for safety reasons:

None known

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### Additional information:

In case of fire, keep containers cool with water spray.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

MSDS-No.: 153474 LOCTITE 648 Page 5 of 20

V005.0

#### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

# 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

#### 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

# Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

## 7.2. Conditions for safe storage, including any incompatibilities

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

## 7.3. Specific end use(s)

Adhesive

MSDS-No.: 153474 LOCTITE 648 Page 6 of 20

V005.0

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	V 1	Short term exposure limit category / Remarks	Regulatory list
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	143	Short Term Exposure Limit (STEL):		EH40 WEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	72	Time Weighted Average (TWA):		EH40 WEL

# **Occupational Exposure Limits**

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit	Regulatory list
				category / Remarks	
Acrylic acid 79-10-7 [ACRYLIC ACID]	2	6	Time Weighted Average (TWA):		IR_OEL
Acrylic acid 79-10-7 [ACRYLIC ACID (PROP-2-ENOIC ACID)]	10	29	Time Weighted Average (TWA):	Indicative	ECTLV
Acrylic acid 79-10-7 [ACRYLIC ACID (PROP-2-ENOIC ACID)]	20	59	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	70	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	140	Short Term Exposure Limit (STEL):		IR_OEL

MSDS-No.: 153474 LOCTITE 648 Page 7 of 20

V005.0

# $\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	Environmental Compartment	Exposure period	Value				Remarks
	- Junear timent	Periou	mg/l	ppm	mg/kg	others	
2,2'-Ethylenedioxydiethyl dimethacrylate	aqua		0,164 mg/l				
109-16-0	(freshwater)						
2,2'-Ethylenedioxydiethyl dimethacrylate	aqua (marine		0,0164				
109-16-0 2,2'-Ethylenedioxydiethyl dimethacrylate	water) sewage		mg/l 10 mg/l				
109-16-0	treatment plant (STP)		10 mg/1				
2,2'-Ethylenedioxydiethyl dimethacrylate	aqua		0,164 mg/l				
109-16-0	(intermittent releases)						
2,2'-Ethylenedioxydiethyl dimethacrylate	sediment				1,85 mg/kg		
109-16-0	(freshwater)				0.105		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sediment (marine water)				0,185 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate	soil				0,274		
109-16-0	5011				mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate	Air						
109-16-0							
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Predator						
Acrylic acid	aqua		0,003 mg/l				
79-10-7	(freshwater)		0.0002				
Acrylic acid 79-10-7	aqua (marine water)		0,0003 mg/l				
Acrylic acid	aqua		0,0013				
79-10-7	(intermittent releases)		mg/l				
Acrylic acid	sewage		0,9 mg/l				
79-10-7	treatment plant (STP)						
Acrylic acid	sediment				0,0236		
79-10-7	(freshwater)				mg/kg		
Acrylic acid 79-10-7	sediment (marine water)				0,00236 mg/kg		
Acrylic acid 79-10-7	soil				1 mg/kg		
Acrylic acid 79-10-7	oral				0,0023 mg/kg		
Acrylic acid	Predator				0,03 g/kg		
79-10-7	Tedator				0,03 g/kg		
Methacrylic acid, monoester with propane-	aqua		0,904 mg/l				
1,2-diol	(freshwater)						
27813-02-1			0.004 //				
Methacrylic acid, monoester with propane- 1,2-diol	aqua (marine water)		0,904 mg/l				
27813-02-1	water)						
Methacrylic acid, monoester with propane-	sewage		10 mg/l				
1,2-diol	treatment plant						
27813-02-1 Methacrylic acid, monoester with propane-	(STP)		0,972 mg/l				
1,2-diol	aqua (intermittent		0,972 mg/1				
27813-02-1	releases)						
Methacrylic acid, monoester with propane-	sediment				6,28 mg/kg		
1,2-diol	(freshwater)						
27813-02-1	11				6.20 #		
Methacrylic acid, monoester with propane- 1,2-diol	sediment (marine water)				6,28 mg/kg		
27813-02-1 Methacrylic acid, monoester with propane-	soil				0,727	-	
1,2-diol 27813-02-1	SOII				mg/kg		
.alpha.,.alphaDimethylbenzyl	aqua		0,0031			1	
hydroperoxide 80-15-9	(freshwater)		mg/l				
.alpha.,.alphaDimethylbenzyl	aqua (marine		0,00031				
hydroperoxide 80-15-9	water)		mg/l				
.alpha.,.alphaDimethylbenzyl	aqua		0,031 mg/l				
hydroperoxide	(intermittent	1		<u> </u>			1

MSDS-No.: 153474 LOCTITE 648 Page 8 of 20

V005.0

100.15.0		1 1	i i	1
80-15-9	releases)			
.alpha.,.alphaDimethylbenzyl	Sewage	0,35 mg/l		
hydroperoxide	treatment plant			
80-15-9				
.alpha.,.alphaDimethylbenzyl	sediment		0,023	
hydroperoxide	(freshwater)		mg/kg	
80-15-9				
.alpha.,.alphaDimethylbenzyl	sediment		0,0023	
hydroperoxide	(marine water)		mg/kg	
80-15-9				
.alpha.,.alphaDimethylbenzyl	soil		0,0029	
hydroperoxide			mg/kg	
80-15-9				
Methacrylic acid	aqua	0,82 mg/l		
79-41-4	(freshwater)	, ,		
Methacrylic acid	aqua (marine	0,82 mg/l		
79-41-4	water)			
Methacrylic acid	sewage	10 mg/l		
79-41-4	treatment plant			
	(STP)			
Methacrylic acid	aqua	0,82 mg/l		
79-41-4	(intermittent	-		
	releases)			
Methacrylic acid	soil		1,2 mg/kg	
79-41-4				

MSDS-No.: 153474 LOCTITE 648 Page 9 of 20

V005.0

# **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	inhalation	Long term exposure - systemic effects		48,5 mg/m3	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	dermal	Long term exposure - systemic effects		13,9 mg/kg	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	inhalation	Long term exposure - systemic effects		14,5 mg/m3	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	dermal	Long term exposure - systemic effects		8,33 mg/kg	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	oral	Long term exposure - systemic effects		8,33 mg/kg	
Acrylic acid 79-10-7	Workers	inhalation	Long term exposure - local effects		30 mg/m3	
Acrylic acid 79-10-7	Workers	inhalation	Acute/short term exposure - local effects		30 mg/m3	
Acrylic acid 79-10-7	Workers	dermal	Acute/short term exposure - local effects		1 mg/cm2	
Acrylic acid 79-10-7	General population	dermal	Acute/short term exposure - local effects		1 mg/cm2	
Acrylic acid 79-10-7	General population	inhalation	Acute/short term exposure - local effects		3,6 mg/m3	
Acrylic acid 79-10-7	General population	inhalation	Long term exposure - local effects		3,6 mg/m3	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	Workers	dermal	Long term exposure - systemic effects		4,2 mg/kg	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	Workers	Inhalation	Long term exposure - systemic effects		14,7 mg/m3	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	General population	Inhalation	Long term exposure - systemic effects		8,8 mg/m3	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	General population	oral	Long term exposure - systemic effects		2,5 mg/kg	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	Workers	inhalation	Long term exposure - systemic effects		6 mg/m3	
Methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - local effects		88 mg/m3	
Methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - systemic effects		29,6 mg/m3	
Methacrylic acid 79-41-4	Workers	dermal	Long term exposure - systemic effects		4,25 mg/kg	
Methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - local effects		6,55 mg/m3	
Methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - systemic effects		6,3 mg/m3	
Methacrylic acid 79-41-4	General population	dermal	Long term exposure - systemic effects		2,55 mg/kg	

MSDS-No.: 153474 LOCTITE 648 Page 10 of 20

V005.0

#### **Biological Exposure Indices:**

None

#### 8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

#### Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

#### Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

#### Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

#### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance liquid liquid

green

Odor characteristic

Odour threshold No data available / Not applicable

pH Not available.

Melting point
No data available / Not applicable
Solidification temperature
No data available / Not applicable

Initial boiling point > 100,0 °C (> 212 °F)

Flash point > 93,3 °C (> 199.94 °F); Tagliabue closed cup

Evaporation rate No data available / Not applicable Flammability No data available / Not applicable Explosive limits No data available / Not applicable

Vapour pressure < 4 mbar

(20 °C (68 °F))

Vapour pressure < 300 mbar

 $(50 \, ^{\circ}\mathrm{C} \, (122 \, ^{\circ}\mathrm{F}))$ 

**LOCTITE 648** MSDS-No.: 153474 Page 11 of 20

Miscible

V005.0

Relative vapour density: No data available / Not applicable

Density 1,13 g/cm3

(25 °C (77 °F))

Bulk density No data available / Not applicable No data available / Not applicable Solubility Not miscible

Solubility (qualitative)

(23 °C (73.4 °F); Solvent: Water)

Solubility (qualitative)

(20 °C (68 °F); Solvent: Acetone)

Partition coefficient: n-octanol/water No data available / Not applicable Auto-ignition temperature No data available / Not applicable No data available / Not applicable Decomposition temperature Viscosity No data available / Not applicable Viscosity (kinematic) No data available / Not applicable Explosive properties No data available / Not applicable Oxidising properties No data available / Not applicable

#### 9.2. Other information

No data available / Not applicable

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Reaction with strong acids. Reacts with strong oxidants.

## 10.2. Chemical stability

Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

See section reactivity

# 10.4. Conditions to avoid

No decomposition if used according to specifications.

## 10.5. Incompatible materials

See section reactivity.

#### 10.6. Hazardous decomposition products

carbon oxides.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

## STOT-single exposure:

May cause respiratory irritation.

## Oral toxicity:

May cause irritation to the digestive tract.

#### Skin irritation:

Causes skin irritation.

Non corrosive to skin in accordance with the in vitro test method, B40 skin corrosion - Human skin model assay, equivalent to test method OECD 431 or based on analogy to similar products tested.

#### Eye irritation:

Causes serious eye damage.

MSDS-No.: 153474 LOCTITE 648 Page 12 of 20

V005.0

# **Sensitizing:**

May cause an allergic skin reaction.

# Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
2,2'-Ethylenedioxydiethyl	LD50	10.837 mg/kg	oral		rat	not specified
dimethacrylate						
109-16-0						
Acrylic acid	LD50	1.500 mg/kg	oral		rat	BASF Test
79-10-7						
Hydroxypropyl	LD50	> 2.000 mg/kg	oral		rat	OECD Guideline 401 (Acute
methacrylate						Oral Toxicity)
27813-02-1						
Cumene hydroperoxide	LD50	550 mg/kg	oral		rat	not specified
80-15-9						
Methacrylic acid	LD50	1.320 mg/kg	oral		rat	OECD Guideline 401 (Acute
79-41-4						Oral Toxicity)
1,4-Naphthalenedione	LD50	190 mg/kg	oral		rat	not specified
130-15-4						

# Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Acrylic acid	LC50	> 5,1 mg/l	Vapor.	4 h	rat	OECD Guideline 403 (Acute
79-10-7		_				Inhalation Toxicity)
Acrylic acid	Acute	11 mg/l	vapour			Expert judgement
79-10-7	toxicity		1			
	estimate					
	(ATE)					
Methacrylic acid	LC50	> 3,6  mg/l	aerosol	4 h	rat	OECD Guideline 403 (Acute
79-41-4						Inhalation Toxicity)

# Acute dermal toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
2,2'-Ethylenedioxydiethyl	LD50	> 2.000 mg/kg	dermal		mouse	not specified
dimethacrylate						
109-16-0						
Acrylic acid	Acute	1.100 mg/kg	dermal			Expert judgement
79-10-7	toxicity					
	estimate					
	(ATE)					
Acrylic acid	LD50	> 2.000 mg/kg			rabbit	OECD Guideline 402 (Acute
79-10-7						Dermal Toxicity)
Hydroxypropyl	LD50	> 5.000 mg/kg	dermal		rabbit	not specified
methacrylate						
27813-02-1						
Cumene hydroperoxide	LD50	1.200 - 1.520	dermal			not specified
80-15-9		mg/kg				
Methacrylic acid	Acute	500 mg/kg	dermal			Expert judgement
79-41-4	toxicity					
	estimate					
	(ATE)					
Methacrylic acid	LD50	500 - 1.000		ĺ	rabbit	Dermal Toxicity Screening
79-41-4		mg/kg				

MSDS-No.: 153474 LOCTITE 648 Page 13 of 20

V005.0

# Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	not irritating	24 h	rabbit	Draize Test
Acrylic acid 79-10-7	highly corrosive	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydroxypropyl methacrylate 27813-02-1	not irritating	24 h	rabbit	Draize Test
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
Methacrylic acid 79-41-4	Category 1A (corrosive)	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

# Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
2,2'-Ethylenedioxydiethyl	not irritating		rabbit	OECD Guideline 405 (Acute
dimethacrylate				Eye Irritation / Corrosion)
109-16-0				
Acrylic acid	corrosive	21 d	rabbit	BASF Test
79-10-7				
Methacrylic acid	Category I		rabbit	Draize Test
79-41-4				

# ${\bf Respiratory\ or\ skin\ sensitization:}$

Hazardous components CAS-No.	Result	Test type	Species	Method
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Acrylic acid 79-10-7	not sensitising	Skin painting test	guinea pig	not specified
Methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

MSDS-No.: 153474 LOCTITE 648 Page 14 of 20

V005.0

# Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Acrylic acid 79-10-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
Hydroxypropyl methacrylate 27813-02-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Hydroxypropyl methacrylate 27813-02-1	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	not specified
Methacrylic acid 79-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Methacrylic acid 79-41-4	negative	inhalation		mouse	OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

# Carcinogenicity:

Hazardous components CAS-No.	Result	Species	Sex	Exposure timeFrequenc y of treatment	Route of application	Method
Hydroxypropyl methacrylate 27813-02-1		rat	male	2 years (102 weeks) 6 hours/day, 5 days/week	inhalation	OECD Guideline 451 (Carcinogenicity Studies)

MSDS-No.: 153474 LOCTITE 648 Page 15 of 20

V005.0

# Reproductive toxicity:

Hazardous substances	Result / Classification	Species	Exposure	Species	Method
CAS-No.			time		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOAEL P = 1.000 mg/kg NOAEL F1 = 1.000 mg/kg	oral: gavage		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Hydroxypropyl methacrylate 27813-02-1	NOAEL P = 400 mg/kg	two- generation study oral: gavage	until one day before sacrifice	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

# Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOAEL=1.000 mg/kg	oral: gavage	daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Hydroxypropyl methacrylate 27813-02-1	NOAEL=300 mg/kg	oral: gavage		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified

# **SECTION 12: Ecological information**

## General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered.

# 12.1. Toxicity

## **Ecotoxicity:**

Harmful to aquatic life with long lasting effects.

Do not empty into drains / surface water / ground water.

MSDS-No.: 153474 LOCTITE 648 Page 16 of 20

V005.0

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
2,2'-Ethylenedioxydiethyl dimehacrylate	LC50	16,4 mg/l	Fish	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute
109-16-0 2,2'-Ethylenedioxydiethyl dimethacrylate	EC50	> 100 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Toxicity Test) OECD Guideline 201 (Alga, Growth
109-16-0	NOEC	18,6 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Inhibition Test) OECD Guideline 201 (Alga, Growth
2,2'-Ethylenedioxydiethyl dimethacrylate	NOEC	32 mg/l	chronic Daphnia	21 d	Daphnia magna	Inhibition Test) OECD 211 (Daphnia magna,
109-16-0 Acrylic acid 79-10-7	LC50	27 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	Reproduction Test EPA OTS 797.1400 (Fish Acute Toxicity Test)
Acrylic acid 79-10-7	EC10	0,03 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus	OECD Guideline 201 (Alga, Growth
	EC50	0,13 mg/l	Algae	72 h	subspicatus) Scenedesmus subspicatus (new name: Desmodesmus	Inhibition Test) OECD Guideline 201 (Alga, Growt Inhibition Test)
Acrylic acid 79-10-7	EC10	41 mg/l	Bacteria	16 h	subspicatus)	not specified
Acrylic acid 79-10-7	NOEC	19 mg/l	chronic Daphnia	21 d	Daphnia magna	EPA OTS 797.1330 (Daphnic Chronic Toxicity Test)
Hydroxypropyl methacrylate 27813-02-1	LC50	493 mg/l	Fish	48 h	Leuciscus idus melanotus	DIN 38412-15
Hydroxypropyl methacrylate 27813-02-1	EC50	> 143 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Hydroxypropyl methacrylate 27813-02-1	EC50	> 97,2 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	> 97,2 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydroxypropyl methacrylate 27813-02-1	EC10	1.140 mg/l	Bacteria	16 h		not specified
Hydroxypropyl methacrylate 27813-02-1	NOEC	45,2 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Tes
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growt Inhibition Test)
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min		not specified
Methacrylic acid 79-41-4	LC50	85 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	EPA OTS 797.1400 (Fish Acute Toxicity Test)
Methacrylic acid 79-41-4	EC50	> 130 mg/l	Daphnia	48 h	Daphnia magna	EPA OTS 797.1300 (Aquati Invertebrate Acut Toxicity Test, Freshwater Daphnids)
Methacrylic acid 79-41-4	NOEC	8,2 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline
	EC50	45 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline

MSDS-No.: 153474 LOCTITE 648 Page 17 of 20

V005.0

Methacrylic acid 79-41-4	EC10	100 mg/l	Bacteria	17 h		not specified
1,4-Naphthalenedio 130-15-4	ne EC50	0,011 mg/l	Algae	72 h	Dunaliella bioculata	OECD Guideline 201 (Alga, Growth Inhibition Test)

# 12.2. Persistence and degradability

# Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	readily biodegradable	aerobic	85 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Acrylic acid 79-10-7	readily biodegradable	aerobic	81 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
	inherently biodegradable	aerobic	100 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Hydroxypropyl methacrylate 27813-02-1	readily biodegradable	aerobic	94,2 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Methacrylic acid 79-41-4	inherently biodegradable	aerobic	100 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
	readily biodegradable	aerobic	86 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
1,4-Naphthalenedione 130-15-4		no data	0 - 60 %	OECD 301 A - F

# 12.3. Bioaccumulative potential / 12.4. Mobility in soil

# **Mobility:**

Cured adhesives are immobile.

# **Bioaccumulative potential:** No data available.

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
2,2'-Ethylenedioxydiethyl	2,3					OECD Guideline 117
dimethacrylate						(Partition Coefficient (n-
109-16-0						octanol / water), HPLC
						Method)
Acrylic acid		3,16				not specified
79-10-7						
Acrylic acid	0,46				25 °C	OECD Guideline 107
79-10-7						(Partition Coefficient (n-
						octanol / water), Shake
						Flask Method)
Hydroxypropyl methacrylate	0,97				20 °C	not specified
27813-02-1						
Cumene hydroperoxide		9,1		calculation		OECD Guideline 305
80-15-9						(Bioconcentration: Flow-
						through Fish Test)
Cumene hydroperoxide	2,16					not specified
80-15-9						
Acetic acid, 2-	0,74					not specified
phenylhydrazide						
114-83-0						
Methacrylic acid	0,93				22 °C	OECD Guideline 107
79-41-4						(Partition Coefficient (n-
						octanol / water), Shake
						Flask Method)
1,4-Naphthalenedione	1,71					not specified
130-15-4						

MSDS-No.: 153474 LOCTITE 648 Page 18 of 20

V005.0

#### 12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
2,2'-Ethylenedioxydiethyl dimethacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
109-16-0	Bioaccumulative (vPvB) criteria.
Acrylic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
79-10-7	Bioaccumulative (vPvB) criteria.
Hydroxypropyl methacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
27813-02-1	Bioaccumulative (vPvB) criteria.
Cumene hydroperoxide	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
80-15-9	Bioaccumulative (vPvB) criteria.
Methacrylic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
79-41-4	Bioaccumulative (vPvB) criteria.

## 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Product disposal:

Collection and delivery to recycling enterprise or other registered elimination institution.

Dispose of in accordance with local and national regulations.

#### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

#### Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

MSDS-No.: 153474 LOCTITE 648 Page 19 of 20

V005.0

# **SECTION 14: Transport information**

## 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

# 14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 5,00 % (2010/75/EC)

# 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

MSDS-No.: 153474 LOCTITE 648 Page 20 of 20

V005.0

# **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.