

## GREEN DIAMOND GRIP NITRILE GLOVES

### 1. Product Description

Made of high quality strong Nitrile, GD535 gloves are designed for high resistance and strong performance, whilst ensuring good dexterity, with a studded palm pattern technology to ensure extra grip.

### 2. Attributes

- Manufactured from nitrile butadiene
- Latex free reducing the risk of hypersensitivity and allergic reactions
- Low in residual chemicals to reduce the risk of contact dermatitis associated with these chemicals
- Flexible material for improved feel and fit reducing fatigue during extended wear
- Tear resistant providing greater durability compared to latex or vinyl
- Beaded cuff for added strength and easier donning
- Powder free to reduce potential dust contamination
- Studded texture to improve grip and performance

### 3. Regulatory Compliance

Manufactured in accordance with:

- European Personal Protective Equipment Directive 89/686/EEC
- CE Category: Cat III (0086)
- EN420: Protective gloves: General requirements
- EN374-2 Protective gloves: Chemicals and Micro organisms penetration
- EN374-3 Protective gloves: Chemicals and Micro organisms permeation

Complies with:

- EN455 parts 1, 2, 3 and 4: Medical gloves for single use

Tested to:

- AQL 1.5
- EN388
- Food approval EC1935/2004

Visually inspected for holes and minor defects

Random samples are filled with 1L of water and examined for leaks

Typical force at break: 9 Newtons

Shelf life of 3 years

Warning: Contains ZDBC and ZDEC chemicals, which can cause type IV skin irritation and contact dermatitis.

## GREEN DIAMOND GRIP NITRILE GLOVES

EN420	Level
Dexterity	5

EN374	Code	Level
Sodium hydroxide 40%	K	6
n-heptane	J	2

### 4. Dimensions

	Small	Medium	Large	Extra Large
Palm Width (mm)	85 ± 10	95 ± 10	110 ± 10	≥ 110 ± 10
Length (mm)	Min 240	Min 240	Min 240	Min 240
Thickness (mm) palm	0.18 ± 0.02	0.18 ± 0.02	0.18 ± 0.02	0.18 ± 0.02
Thickness (mm) finger	0.20 ± 0.02	0.20 ± 0.02	0.20 ± 0.02	0.20 ± 0.02
Thickness (mm) cut	0.10 ± 0.02	0.10 ± 0.02	0.20 ± 0.02	0.20 ± 0.02

EN420: glove measurements are determined by taking into account the behaviour of the glove material and intended use.



















### 5. Packing

Inner: 100 gloves per dispenser

Outer: 10 dispensers per case

Pallet: 40 cases per pallet

### 6. Symbols

 Lot number	 Compliant with the Personal Protective Equipment Directive	 EN420: Protective gloves: General requirements	 Temperature limitation
 Date of manufacture	 Non-sterile	 EN374 - 2: Micro organism hazards	 Recyclable packaging
 Use by	 Acceptable quality level	 EN374 - 3: Chemical hazards	 Keep dry
 Manufacturer	 Latex free	 Food approved	 Keep away from direct sunlight and fluorescent lighting
 Do not re-use	 Powder free		