



## Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 15

LOCTITE SF 7649 PRIMER known as LOCTITE® 7649™  
PRIMER

SDS No. : 153666  
V004.0

Revision: 24.10.2016

printing date: 13.09.2017

Replaces version from: 28.09.2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE SF 7649 PRIMER known as LOCTITE® 7649™ PRIMER

#### Contains:

Acetone

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:  
activator

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd  
Wood Lane End  
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000  
Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Flammable aerosols	Category 1
H222 Extremely flammable aerosol.	
H229 Pressurised container: May burst if heated.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central Nervous System	

#### 2.2. Label elements

##### Label elements (CLP):

**Hazard pictogram:**



**Signal word:**

Danger

**Hazard statement:**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H336 May cause drowsiness or dizziness.  
H319 Causes serious eye irritation.

**Precautionary statement:**

P251 Do not pierce or burn, even after use.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P211 Do not spray on an open flame or other ignition source.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P102 Keep out of reach of children.  
\*\*\*For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements\*\*\*

**Precautionary statement:  
Prevention**

P261 Avoid breathing spray.

**Precautionary statement:  
Response**

P337+P313 If eye irritation persists: Get medical advice/attention.

**2.3. Other hazards**

The aerosol container is under pressure. Do not expose to high temperatures.  
Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**General chemical description:**

Solvent based activator.

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Acetone 67-64-1	200-662-2 01-2119471330-49	50- 100 %	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336
Butane, n- (< 0.1 % butadiene) 106-97-8	203-448-7 01-2119474691-32	10- 20 %	Flam. Gas 1 H220 Press. Gas
Propane 74-98-6	200-827-9 01-2119486944-21	10- 20 %	Flam. Gas 1 H220 Press. Gas H280
2-Ethylhexanoic acid 149-57-5	205-743-6 01-2119488942-23	0,1- < 1 %	Repr. 2 H361d
Tributyl amine 102-82-9	203-058-7 01-2119474898-14	0,1- < 1 %	Acute Tox. 4; Oral H302 Acute Tox. 2; Dermal H310 Skin Irrit. 2 H315 Acute Tox. 1; Inhalation H330
Copper(II) carbonate--copper(II) hydroxide (1:1) 12069-69-1	235-113-6 01-2119513711-50	0,1- < 0,25 %	Aquatic Acute 1 H400 Aquatic Chronic 1 H410 Acute Tox. 4; Oral H302 Eye Irrit. 2 H319 Acute Tox. 4; Inhalation H332 M factor (Acute Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information".  
Substances without classification may have community workplace exposure limits available.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

## Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

## Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

## Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

## Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

EYE: Irritation, conjunctivitis.

Prolonged or repeated contact may cause skin irritation.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

**5.2. Special hazards arising from the substance or mixture**

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid skin and eye contact.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

**6.2. Environmental precautions**

Do not let product enter drains.

**6.3. Methods and material for containment and cleaning up**

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Vapours should be extracted to avoid inhalation.

Keep away from sources of ignition - no smoking.

Avoid skin and eye contact.

See advice in section 8

**Hygiene measures:**

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a cool, well-ventilated place.

Keep away from heat and direct sunlight.

**7.3. Specific end use(s)**

activator

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetone 67-64-1 [ACETONE]	1.500	3.620	Short Term Exposure Limit (STEL):		EH40 WEL
Acetone 67-64-1 [ACETONE]	500	1.210	Time Weighted Average (TWA):		EH40 WEL
Acetone 67-64-1 [ACETONE]	500	1.210	Time Weighted Average (TWA):	Indicative	ECLTV
Butane 106-97-8 [BUTANE]	750	1.810	Short Term Exposure Limit (STEL):		EH40 WEL
Butane 106-97-8 [BUTANE]	600	1.450	Time Weighted Average (TWA):		EH40 WEL

**Occupational Exposure Limits**Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetone 67-64-1 [ACETONE]	500	1.210	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Acetone 67-64-1 [ACETONE]	500	1.210	Time Weighted Average (TWA):	Indicative	ECLTV
Butane 106-97-8 [BUTANE]	1.000		Time Weighted Average (TWA):		IR_OEL
Propane 74-98-6 [PROPANE]	1.000		Time Weighted Average (TWA):		IR_OEL
2-Ethylhexanoic acid 149-57-5 [ETHYL HEXANOIC ACID]		4	Time Weighted Average (TWA):		IR_OEL

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Acetone 67-64-1	aqua (intermittent releases)					21 mg/L	
Acetone 67-64-1	sewage treatment plant (STP)					100 mg/L	
Acetone 67-64-1	sediment (freshwater)				30,4 mg/kg		
Acetone 67-64-1	sediment (marine water)				3,04 mg/kg		
Acetone 67-64-1	soil				29,5 mg/kg		
Acetone 67-64-1	aqua (freshwater)					10,6 mg/L	
Acetone 67-64-1	aqua (marine water)					1,06 mg/L	
2-Ethylhexanoic acid 149-57-5	aqua (freshwater)					0,36 mg/L	
2-Ethylhexanoic acid 149-57-5	aqua (marine water)					0,036 mg/L	
2-Ethylhexanoic acid 149-57-5	aqua (intermittent releases)					0,493 mg/L	
2-Ethylhexanoic acid 149-57-5	sewage treatment plant (STP)					71,7 mg/L	
2-Ethylhexanoic acid 149-57-5	sediment (freshwater)				6,37 mg/kg		
2-Ethylhexanoic acid 149-57-5	sediment (marine water)				0,637 mg/kg		
2-Ethylhexanoic acid 149-57-5	soil				1,06 mg/kg		
Tributyl amine 102-82-9	aqua (freshwater)					0,0036 mg/L	
Tributyl amine 102-82-9	aqua (marine water)					0,00036 mg/L	
Tributyl amine 102-82-9	sediment (freshwater)				16,9 mg/kg		
Tributyl amine 102-82-9	sediment (marine water)				1,69 mg/kg		
Tributyl amine 102-82-9	aqua (intermittent releases)					0,036 mg/L	
Tributyl amine 102-82-9	soil				3,37 mg/kg		
Tributyl amine 102-82-9	sewage treatment plant (STP)					100 mg/L	

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Acetone 67-64-1	Workers	Inhalation	Acute/short term exposure - local effects		2420 mg/m <sup>3</sup>	
Acetone 67-64-1	Workers	dermal	Long term exposure - systemic effects		186 mg/kg bw/day	
Acetone 67-64-1	Workers	Inhalation	Long term exposure - systemic effects		1210 mg/m <sup>3</sup>	
Acetone 67-64-1	General population	dermal	Long term exposure - systemic effects		62 mg/kg bw/day	
Acetone 67-64-1	General population	Inhalation	Long term exposure - systemic effects		200 mg/m <sup>3</sup>	
Acetone 67-64-1	General population	oral	Long term exposure - systemic effects		62 mg/kg bw/day	
2-Ethylhexanoic acid 149-57-5	Workers	dermal	Long term exposure - systemic effects		12 mg/kg bw/day	
2-Ethylhexanoic acid 149-57-5	Workers	Inhalation	Long term exposure - systemic effects		32 mg/m <sup>3</sup>	
2-Ethylhexanoic acid 149-57-5	General population	dermal	Long term exposure - systemic effects		6 mg/kg bw/day	
2-Ethylhexanoic acid 149-57-5	General population	Inhalation	Long term exposure - systemic effects		8 mg/m <sup>3</sup>	
2-Ethylhexanoic acid 149-57-5	General population	oral	Long term exposure - systemic effects		2,5 mg/kg bw/day	
Tributyl amine 102-82-9	Workers	inhalation	Long term exposure - systemic effects		15,2 mg/m <sup>3</sup>	
Tributyl amine 102-82-9	Workers	inhalation	Long term exposure - local effects		15,2 mg/m <sup>3</sup>	

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:  
Ensure good ventilation/extraction.

Respiratory protection:  
Ensure adequate ventilation.  
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area  
Filter type: A (EN 14387)

**Hand protection:**

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq$  0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq$  0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

**Skin protection:**

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	aerosol green
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Initial boiling point	56 °C (132.8 °F)
Flash point	-20 °C (-4 °F); Estimated
Decomposition temperature	No data available / Not applicable
Vapour pressure (20 °C (68 °F))	230 mbar
Density	No data available / Not applicable
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Soluble
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

**9.2. Other information**

No data available / Not applicable



**SECTION 10: Stability and reactivity****10.1. Reactivity**

Reacts with strong oxidants.

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

See section reactivity

**10.4. Conditions to avoid**

Stable under normal conditions of storage and use.

**10.5. Incompatible materials**

See section reactivity.

**10.6. Hazardous decomposition products**

Irritating organic vapours.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****General toxicological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

**STOT-single exposure:**

May cause drowsiness or dizziness.

**Oral toxicity:**

May cause irritation to the digestive tract.

**Skin irritation:**

Prolonged or repeated contact may cause skin irritation.

**Eye irritation:**

Causes serious eye irritation.

**Acute oral toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Acetone 67-64-1	LD50	5.800 mg/kg	oral		rat	not specified
2-Ethylhexanoic acid 149-57-5	LD50	3.640 mg/kg	oral		rat	BASF Test
Tributyl amine 102-82-9	LD50	320 mg/kg	oral		mouse	
Tributyl amine 102-82-9	LD50	420 mg/kg			rat	not specified
Copper(II) carbonate-- copper(II) hydroxide (1:1) 12069-69-1	LD50	1.291 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)

**Acute inhalative toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Acetone 67-64-1	LC50	76 mg/l		4 h	rat	not specified
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	658 mg/l		4 h	rat	not specified
Propane 74-98-6	LC50	619 mg/l		4 h	mouse	not specified
Tributyl amine 102-82-9	LC50	0,5 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

**Acute dermal toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Acetone 67-64-1	LD50	> 15.688 mg/kg	dermal		rabbit	Draize Test
2-Ethylhexanoic acid 149-57-5	LD50	> 2.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)
Tributyl amine 102-82-9	LD50	195 mg/kg	dermal		rabbit	not specified
Copper(II) carbonate-- copper(II) hydroxide (1:1) 12069-69-1	LD50	> 2.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)

**Skin corrosion/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Acetone 67-64-1	not irritating		guinea pig	not specified
2-Ethylhexanoic acid 149-57-5	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Acetone 67-64-1	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-Ethylhexanoic acid 149-57-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

Hazardous components CAS-No.	Result	Test type	Species	Method
Acetone 67-64-1	not sensitising	Guinea pig maximisation test	guinea pig	not specified

**Germ cell mutagenicity:**

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Acetone 67-64-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
	negative	mammalian cell gene mutation assay	without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Acetone 67-64-1	negative	oral: drinking water		mouse	not specified
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative			Drosophila melanogaster	not specified
Propane 74-98-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Propane 74-98-6	negative			Drosophila melanogaster	not specified
2-Ethylhexanoic acid 149-57-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Ames Test

**Carcinogenicity:**

Hazardous components CAS-No.	Result	Species	Sex	Exposure time Frequency of treatment	Route of application	Method
Acetone 67-64-1	not carcinogenic	mouse	female	424 d 3 times per week	dermal	not specified

**Repeated dose toxicity**

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Acetone 67-64-1	NOAEL=900 mg/kg	oral: drinking water	13 wdaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Butane, n- (< 0.1 % butadiene) 106-97-8		inhalation: gas	28 d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propane 74-98-6		inhalation: gas	28 d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

**SECTION 12: Ecological information****General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

**12.1. Toxicity****Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Acetone 67-64-1	LC50	8.120 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Acetone 67-64-1	EC50	8.800 mg/l	Daphnia	48 h	Daphnia pulex	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Acetone 67-64-1	NOEC	530 mg/l	Algae	8 d	Microcystis aeruginosa	DIN 38412-09
Acetone 67-64-1	EC10	1.000 mg/l	Bacteria	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
Acetone 67-64-1	NOEC	2.212 mg/l	chronic Daphnia	28 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	27,98 mg/l	Fish	96 h		not specified
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	14,22 mg/l	Daphnia	48 h		not specified
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	7,71 mg/l	Algae	96 h		not specified
2-Ethylhexanoic acid 149-57-5	LC50	270 mg/l	Fish	96 h	Lepomis gibbosus	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Ethylhexanoic acid 149-57-5	EC50	85,4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Ethylhexanoic acid 149-57-5	EC50	61 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Ethylhexanoic acid 149-57-5	EC10	33 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Ethylhexanoic acid 149-57-5	EC10	72 mg/l	Bacteria	17 h		DIN 38412, part 8 (Pseudomonas Zellvermehrungshe mm-Test)
Tributyl amine 102-82-9	LC50	60,2 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
Tributyl amine 102-82-9	EC50	8 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Tributyl amine 102-82-9	EC10	1,378 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Tributyl amine 102-82-9	EC50	8,215 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Tributyl amine 102-82-9	EC0	> 800 mg/l	Bacteria	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Copper(II) carbonate-- copper(II) hydroxide (1:1) 12069-69-1	LC50	> 0,1 - 2,5 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Copper(II) carbonate-- copper(II) hydroxide (1:1) 12069-69-1	EC10	0,32 mg/l	Bacteria			not specified

**12.2. Persistence and degradability****Persistence and Biodegradability:**

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Acetone 67-64-1	readily biodegradable	aerobic	81 - 92 %	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
2-Ethylhexanoic acid 149-57-5		aerobic	> 70 %	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
	readily biodegradable	aerobic	99 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Tributyl amine 102-82-9		aerobic	< 10 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
	inherently biodegradable	aerobic	94 %	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
	readily biodegradable	aerobic	80,3 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

**12.3. Bioaccumulative potential / 12.4. Mobility in soil****Mobility:**

The product evaporates readily.

**Bioaccumulative potential:**

No data available.

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Acetone 67-64-1	-0,24					OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2-Ethylhexanoic acid 149-57-5	2,7					OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Tributyl amine 102-82-9	3,338				25 °C	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow-Stirring Method)

**12.5. Results of PBT and vPvB assessment**

Hazardous components CAS-No.	PBT/vPvB
Acetone 67-64-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Butane, n- (< 0.1 % butadiene) 106-97-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Propane 74-98-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-Ethylhexanoic acid 149-57-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Tributyl amine 102-82-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Copper(II) carbonate--copper(II) hydroxide (1:1) 12069-69-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**12.6. Other adverse effects**

No data available.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Collection and delivery to recycling enterprise or other registered elimination institution.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

14 06 03 - other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

**SECTION 14: Transport information****14.1. UN number**

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

**14.2. UN proper shipping name**

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

**14.3. Transport hazard class(es)**

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

**14.4. Packing group**

ADR  
RID  
ADN  
IMDG  
IATA

**14.5. Environmental hazards**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.6. Special precautions for user**

ADR	not applicable
-----	----------------

	Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content 100 %  
(2010/75/EC)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapor.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

**Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**