Page 1 of 8

1. Substance/preparation and company description Brand name/part number of product

SACHS 314 725

Details of manufacturer/supplier:

Address of manufacturer/supplier:

ZF Friedrichshafen AG Ernst-Sachs-Straße 62 97424 Schweinfurt ☎ (0049)(0)9721/98-0

Information from: (00)(0)9721/98-3454

Mr. Dr. Schreiner Dept. Environmental Protection

Emergency information / Emergency number: Closest poisoning treatment centre, info: Mineral oil contact

2. Composition / info. on components Chemical characteristics (preparation)

% Wt.	% Vol.	Chemical desc.	Haz. sym.	R sets
		Various mineral oils		
		Compressed air		
		Aluminum tube		

The following information refers to the damper oil.

3. Possible hazards

Description of hazards: Intensive, lengthy and repeated skin contact can lead to skin irritation.

Safety risks: Avoid formation of oil mist.

Environmental hazards: Do not allow to escape uncontrolled into the environment. Damper oil is not completely biologically degradable. **SAFETY DATA SHEET** conforming with 91/155/EWG Date: 10.08.2000 Last revision on: 01.02.2013 Data sheet identification: D 05

Brand name: Twintube shock absorber

Page 2 of 8

Page 3 of 8

4. First-aid measures

General information: Can cause loss of natural grease and irritation if in contact with the skin for some time.

After inhalation: Fresh air. Call doctor if symptoms persist.

After skin contact: Rinse well with soap and water. Intensive skin care required.

After eye contact: Rinse immediately with lots of water (10 min.)

After swallowing: Do not induce vomiting, call doctor.

Information for the doctor: Symptomatic treatment.

5. Fire-fighting measures

Suitable extinguishing materials: Ensure that extinguishing material is suitable for background fires

Unsuitable extinguishing materials for safety reasons:

Special hazards due to the material or combustion products: Container is under pressure. Cool it with water spray if affected by fire.

Special protective equipment required for fire-fighting: Ensure that protective equipment is suitable for background fires

6. Measures if unintentionally released

Personal safety measures: Avoid skin contact with damper oil. Immediately change contaminated working clothes.

Environmental measures: Protect sewers and surface water from damper oil.

Page 4 of 8

Procedures for cleaning: Use oil absorbing material and dispose contaminated material according to the regulations.

Supplementary advice: None

7. Handling and storage

Handling: Do not open containers, do not heat product, do not throw product or assemble/disassemble by force. Storage:

Store in clean and dry areas.

8. Exposure limits and personal protection equipment

Supplementary advice for the configuration of technical plant:

Components with workplace-related limits which must be monitored:

Limits	Chem. description

Personal protection equipment

Breathing protection:	Only if oil mist escapes
Eye protection:	Wear safety goggles if risk of spraying
Skin protection:	Only in the case of lengthy skin contact
Other:	

Page 5 of 8

9. Physical and chemical characteristics Damper oil

Form: Liquid	Colour: various	Odour: Like mineral oil
Change in physical state: Melting point or range Boiling point or range	max45 ºC ⁰C	Tested acc. to
Density: Bulk density:	approx. 0.85 g/ccm	ı
Vapour pressure: For aerosols & gases: Values at 20 °C	< 0.1 mbar	
Viscosity:	11 – 60 mm²/ s	
Solvent separation test:	smaller greater/sam	ne3 %
Solids content:	%	
Solubility:	Virtually insoluble	
pH value:	not applicable	
Flashpoint:	120 - 180 °C	
Ignition temperature:	٥C	
Explosion limits in air:	Lower 0.6% Upper 6.5%	
Thermal decomposition:	above 360 °C	
Decomposition products: Prop. by weight %		
Dangerous reactions (with):	Possible reaction with strong of	oxidizers
Additional information:		

Page 6 of 8

10. Stability and reactivity

Conditions to avoid: Damper oil is stable if used as specified

Substances to avoid: Avoid contact with strong oxidizers.

Hazardous decomposition products: No hazardous decomposition products under normal conditions

Additional information: In the case of frequent skin contact use personal protection equipment. (Gloves, protective and care creams, liquid soap)

11. Toxicological information

Toxicological testing: LD50, oral - rats > 5000 mg/kg LD50, dermal - rabbits > 3000 mg/kg

12. Ecological information

Elimination details (persistence and degradability):

Behaviour in environmental compartments:

Ecotoxic effect: Further information on ecology: WGK2

13. Disposal information

Product:Steel parts:160117 steel scrapAluminum parts:160118 aluminum scrapDamper oil:130113 other waste oil / hydraulic oilPlastic and rubber parts:160119 plastic and rubber wasteUncleaned packages:not applicable

Page 7 of 8

			Page 7 o
•	regulations sport (roa	d/rail, national an	d international)
ADR/RID/G Warning sig Proper Shippi flammable ga	gn: - ng Name: ART		Classification Code: 6A b.: - UN no.: UN 3164 ED, PNEUMATIC (containing non-
Remarks: 1	he release o	conditions of 594	4 and 283 are fulfilled.
Transport	by Inland wa	aterways	
ADN/ADNF	R	Class: 2	Classification Code: 6A UN no.: UN 3164
Proper Shippi flammable ga		ICLES, PRESSURIZ	ED, PNEUMATIC (containing non-
Remarks: The releas	e conditions	s of 594 and 283	are fulfilled.
Ocean-goi	ng ship tran	sport	
IMDG/GGV	'See	Class: 2.2 PG: - EMS: -	UN no.: UN 3164
Marine poll Proper Ship	utant: oping Name:	No Articles , pi non-flamma	ressurized, pneumatic, containing able gas
		conditions of 283 4 can be used acc	3 are fulfilled. cording to the gas volume.
Air transp	ort		
ICAO/IATA		Class: 2.2	UN no.: UN 3164
Proper Ship flammable		Articles , pressur	ized, pneumatic, containing non-
Remarks:	The release	conditions of A	114 are fulfilled.
Postal trans	sport		
		general postal dia ail, national / inte	

Page 8 of 8

15. Regulations

Certification acc. to EU guidelines: Referring to damper oil

National regulations.

Classification acc. to Vbf :	No
Tech. instructions - AIR (TA-Luft):	Class 3
Water balance law	WGK 2, water-hazard
Employment restrictions :	None
Incident regulations:	-

16. Miscellaneous

Further information:Tolerance values from the professional institute for health and safety at work:Aerosol concentration5 mg/cbmVapour and aerosol conc.20 mg/cbm

The standard safety measures for handling mineral oil products must be followed.

There is no legal duty to provide the information in this data sheet (see Section 15).

The information is provided voluntarily and with the best of the knowledge available at the date of the revision.

It does not guarantee the retention of particular properties within the meaning of a legal obligation.